



ESGARD RUST CONVERTER

DESCRIPTION

Rust Converter is a liquid zinc phosphate solution that promotes corrosion inhibition and converts red rust (ferrous oxide) to the more stable black rust (ferric oxide). Product advantages include:

1. Treated surfaces need not be washed or cleaned again prior to paint application.
2. No powdery residue.
3. No latex resins to interfere with adhesion of applied coatings.

FIELD OF APPLICATION

For use on ferrous metal surfaces to stabilize any remaining red rust on hand or power tool cleaned surfaces prior to paint application.

TECHNICAL DATA

TYPE	Zinc oxide/Phosphoric acid solution
V.O.C.	0.81 lb/gal (97 g/l)
DENSITY	9.79 lb/gal mixed (1.17 kg/l)
DRY TIME	3 - 5 hours @ 77°F (25°C) 80% R.H.

SURFACE PREPARATION

Thoroughly clean any oil or grease contaminated areas. Remove all rust scale to expose sound base metal using the most economical methods.

APPLICATION

Apply full strength from a non-metallic container by brushing or swabbing to thoroughly wet the surfaces. Allow to dry completely before painting.

CLEAN UP

Use soap and water.

ORDERING INFORMATION

CONTACT # 1-800-888-2511

SHIPPING WEIGHT

	<u>1 GAL</u>	<u>5 GAL</u>
Rust Converter	10.1 lb (4.6 kg)	52.0 lb (23.6 kg)

FLASH POINT Not applicable.

COLORS Clear

SHELF LIFE Twelve (12) months from date of shipment.

Manufacturers of Quality Paints, Protective Coatings, and Lubricants
Esgard, Inc. 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337) 234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgard.com



CAUTION **FOR INDUSTRIAL USE ONLY! CORROSIVE!** Contains phosphoric acid and nitric acid.

SAFETY: Refer to material safety data sheet supplied with each order

FIRST AID Refer to Material Safety Data Sheet supplied with each order.

Manufacturers of Quality Paints, Protective Coatings, and Lubricants
Esgard, Inc. 515 Debonnaire Road Scott, Louisiana 70583 U.S.A.
(337) 234-6327 Fax (337) 234-0113 1-800-888-2511

www.esgard.com